



PRODUCT INFORMATION



Product Name:	WATER BASED CLEAR POLYURETHANE VARNISH
Reference Number:	8-53 Silk 8-54 Gloss
Coating Type:	Water Based Polyurethane Clear Varnish
Typical Uses:	A tough, durable, hard wearing, single pack coating for wooden floors, worktops, joinery etc. As a clear sealer/finish to prevent dusting on concrete floors.
Colours Available:	Clear
Appearance of Dried Film:	Silk or Gloss
Volume Solids:	31%
Theoretical Coverage:	8-10 m ² / litre. Will vary depending on porosity of substrate.
Drying Time at 20°C: (Will vary with temperature, air movement etc.)	Touch Dry: 1 hour. Firm Dry: 2-2 ½ hours. Overcoat: 3-3 ½ hours minimum.
Packaging:	5 litre containers
Shelf Life:	2 years in unopened containers, when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5°C to 32°C.
V.O.C.'s:	125 gms / litre
	Continued/



Surface Preparation:

Previously Coated Floors

Ensure existing coating is firm and sound with good adhesion. Thoroughly clean with detergent water, rinse with clean water and allow to dry.

New Floors

Ensure surface is clean and dry. Apply a minimum of two coats.

Application:

By brush or roller

Clean Up:

Clean water.

Health and Safety:

Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

Issued: October 2003

KW/DAE/WHC