

PRODUCT DATASHEET

Dac Strippable Booth Coating

PRODUCT INFORMATION

Reference Number:

19-2

Coating type:

Dac Strippable Booth Coating is a white pigmented temporary protective coating designed for application to all smooth, clean, metal spray booth walls to provide an easy method of booth maintenance.

Typical uses:

The dried film is readily peelable and enables even heavy overspray deposits to be quickly and cleanly removed.

Exposed areas can then be touched in or the entire area resprayed as necessary.

By providing a white, light reflective surface, better working conditions are obtained making for consistent achievement of high quality work.

Features and benefits:

- Strong easily peelable film
- Enables heavy overspray to be removed quickly and cleanly
- Light reflective surface for better working conditions
- Reduces maintenance time

Theoretical coverage:

2-3m² per litre at 2-3 microns dry film thickness

Drying time will vary with temperature, air movement, etc.

APPLICATION

Use as supplied, stirring thoroughly before use to disperse any settled pigment.

Apply by conventional spraying techniques using normal pressure spraying equipment, pot pressure 20psi, air pressure 40-60psi, and using a 70 thou tip with appropriate air cap and needle.

Apply a double-pass, wet-on-wet, to give a dense white film. Do not dry spray as this may lead to some film shrinkage and poor peelability.

Do not use suction feed guns.

Clean-up:

After use, clean all equipment with Dacrylate Thinner R30.

STORAGE AND PACKAGING

Storage:

Under cover within temperature range of 5°C to 32°C.

Keep containers dry and tightly sealed to avoid moisture contamination.

Shelf life:

2 years in unopened containers when stored under cover within a temperature range of 5°C to 32°C.

HEALTH AND SAFETY

Please refer to the following data sheets:

019-002 20418 Strippable Booth

All work involving the application and use of this product should be performed in compliance with all relevant national, health, safety & environmental standards, and regulations

ADDITIONAL NOTES

The application and spray information given above is intended as a guide only. As conditions vary from job-to-job, it is the applicators responsibility to ensure all equipment in use has been set up to give the best results.

IMPORTANT INFORMATION

The information supplied in this product datasheet is not intended to be exhaustive. Any person using the product for any other purpose than that specifically recommended in this product datasheet, without first obtaining written confirmation from Dacrylate Technical Services as to the suitability of the product for the intended purpose does so at their own risk. All advice given about the product is correct to the best of our knowledge, however we have no control over the condition of the substrate, preparation or the many factors affecting the use and application of the product. Therefore, unless specifically agreed in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to the maximum extent permitted by law) any loss or damage arising out of the use of the product.

Dacrylate warrants its products to be free from defects in material and workmanship. Dacrylate's obligations and buyer's exclusive remedy relating to the products shall be limited, at Dacrylate's option, to either replace the products not conforming the warranty or the credit of the buyers account in the invoiced amount of the non-conforming product. Any claim under this warranty must be made by the Buyer to Dacrylate in writing within five (5) days of the Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. The Buyer's failure to notify Dacrylate of such non-conformance as required herein shall bar the Buyer from recovery under this warranty.

The information detailed in this datasheet is liable to modification from time-to-time in the light of experience and our programme of product development. Before use, it is the customers responsibility to check with Dacrylate Customer Services, quoting the product reference number and version reference at the bottom of the data sheet, to ensure that they have in their possession the latest issue.

Technical product datasheets are available from our website at www.dacrylate.co.uk, and should be the same as this datasheet. Should there be any discrepancies between this document and the website version, then please contact Dacrylate Customer Services.

© Dacrylate Paints Ltd. 2017

Lindley's Lane, Kirkby-in-Ashfield, Nottinghamshire NG17 8AL. Tel.: 01623 753845 Email: sales@dacrylate.co.uk

www.dacrylate.co.uk