

## TECHNICAL PRODUCT DATASHEET

# Masonry Sealer

**Dacrylate Clear Fungicidal Masonry Sealer** is a water-based acrylic with fungicidal additive primarily for use with water-based Dacrylate masonry coating systems. The sealer penetrates porous substrates such as aged friable masonry paints, new concrete, rendering, brick, plaster and similar.

### PRODUCT INFORMATION

**Coating type:**

Water-based modified acrylic with fungicidal additive for use with water-based coating system.

**Reference number:**

150-50

**Colours available:**

Clear finish only  
Available with white 'tracer' (Ref. 150-429)

### TECHNICAL INFORMATION

**Application rate:**

Low porosity (ie. old emulsion paint)	High porosity (ie. new brick, concrete)
8-10m <sup>2</sup> per litre approx.	4-6m <sup>2</sup> per litre approx.

Dependent on porosity, absorption, etc.

**Drying time:**

Touch dry	Firm dry	Overcoat
30mins	2hrs	2hrs

Drying time at 20°C, will vary with temperature, air movement, etc.

### SURFACE PREPARATION

Remove all loose flaking paint, friable material, etc., by scraping, wire brushing, or similar; to leave sound surfaces. Wash down with detergent water followed by clean water rinse. Allow to dry.

Areas susceptible to fungal growth should be scraped clean and treated with 20% domestic bleach solution followed by clean water rinse.

### APPLICATION

Apply liberally by brush. Brush well into textured surfaces, mortar courses, etc. May be applied by spray to large areas.

**Clean-up:**

Water

---

## STORAGE AND PACKAGING

**Storage:**

Under cover within temperature range of 5°C to 32°C.  
Keep containers dry and tightly sealed to avoid moisture contamination.

**Shelf life:**

2 years or longer in unopened containers when stored under cover within a temperature range of 5°C to 32°C or 'use by' date on packaging.

**Packaging:**

5 litre containers

---

## HEALTH AND SAFETY

Please refer to the following data sheets (*please quote 6-digit number when requesting copies*):

**Clear Fungicidal Sealer (150-50) 10413**

*All work involving the application and use of this product should be performed in compliance with all relevant national, health, safety & environmental standards, and regulations*

---

## ADDITIONAL NOTES

Clear Fungicidal Masonry Sealer should NOT be applied in wet, damp conditions or if rain is threatened.

Relative humidity should be less than 85%.

Ambient temperature should be above 5°C until coating has fully dried.

The application and spray information given above is intended as a guide only. As conditions vary from job-to-job, it is the applicators responsibility to ensure all equipment in use has been set up to give the best results.

---

## IMPORTANT INFORMATION

The information supplied in this product datasheet is not intended to be exhaustive. Any person using the product for any other purpose than that specifically recommended in this product datasheet, without first obtaining written confirmation from Dacrylate Technical Services as to the suitability of the product for the intended purpose does so at their own risk. All advice given about the product is correct to the best of our knowledge, however we have no control over the condition of the substrate, preparation or the many factors affecting the use and application of the product. Therefore, unless specifically agreed in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to the maximum extent permitted by law) any loss or damage arising out of the use of the product.

Dacrylate warrants its products to be free from defects in material and workmanship. Dacrylate's obligations and buyer's exclusive remedy relating to the products shall be limited, at Dacrylate's option, to either replace the products not conforming the warranty or the credit of the buyers account in the invoiced amount of the non-conforming product. Any claim under this warranty must be made by the Buyer to Dacrylate in writing within five (5) days of the Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. The Buyer's failure to notify Dacrylate of such non-conformance as required herein shall bar the Buyer from recovery under this warranty.

The information detailed in this datasheet is liable to modification from time-to-time in the light of experience and our programme of product development. Before use, it is the customers responsibility to check with Dacrylate Customer Services, quoting the product reference number and version reference at the bottom of the data sheet, to ensure that they have in their possession the latest issue.

Technical product datasheets are available from our website at [www.dacrylate.co.uk](http://www.dacrylate.co.uk) and should be the same as this datasheet. Should there be any discrepancies between this document and the website version, then please contact Dacrylate Customer Services.

© **Dacrylate Paints Ltd. 2021**

Lindley's Lane, Kirkby-in-Ashfield, Nottinghamshire NG17 8AL. Tel: 01623 753845 Email: [enquiries@dacrylate.co.uk](mailto:enquiries@dacrylate.co.uk)

[www.dacrylate.co.uk](http://www.dacrylate.co.uk)